Embrace a new world of Learning

Have all the essential tools you need for effective interactive lessons.



LOGIBIRD Next Generation Display



6514ED-1Pro | 7514ED-1Pro | 8614ED-1Pro



1 -







Handwriting Recognition

gnition Type-C charging

In-Built Paint

Elevating Next-Gen Learning with Android 14

Introducing the Logibird Pro series for dynamic classrooms, featuring collaborative tools and connectivity options to create interactive learning spaces. With paper-like writing tech and powered by Android 14 with 8GB RAM and 128GB ROM, lessons come alive ef ortlessly.

Elevate your classroom with Logibird Pro series.



Harness the power of Google

Streamlined teaching with Google

The EDLA- Certified Board combines Google services with ever-reliable hardware and software.



Essential tools for every teacher

All hand on board

The large Interactive screen is designed for whole-class participation, letting you boost engagement and liven up your lessons.



40 touch points

Get everyone actively participating in class with the 40 touch points.



Gap-free writing

No gaps and an 8ms response time ensure a natural writing experience every time



Precise touch

You're guaranteed smooth interactions with the board's Precision technology.

Interactive Flat Panel Technical Specifcation

	Models	;	LB6514ED-1Pro
	Display Size		65"
-	Operating System		Android 14.0
	Technology		Zero Bonding Technology
	Life Span		≥ 80,000 Hours
	Display Cover		Anti-glare with 7H Hardness
	Screen Technology		D-LED Backlit
Panel	Panel Technology		IPS
	Resolution		3840 X 2160 (4K Ultra HD)
	Response Time		<5MS
	System Hardware		Quad Core ARM Cortex A73x4, 8 GB RAM, 128 GB ROM
_	Writing Tools		Finger, Finger Cover By Glove, Opaque Objects
	Aspect Ratio		16:9
-	Active Display Ares (mm)		1428.48 x 803.52
	Brightness (Typical) cd / m²		450
	Contrast Ratio		5000:1
-	Dynamic Contrast		100000:1
-	Viewing Angle (Degree)		178°/ 178°
-	Technology		Infrared optical
Touch	Point		10 / 20 Point Multitouch
	Output Coordinate		32767 x 32767
	Input	HDMI INPUT	3
		VGA	1
Connectivity		Audio	1
		Bluetooth	1
	Output	Audio	1
		OPS Slot	Available

	Input / Output		RJ45 LAN & Wi-Fi
			RS232
			USB 2.0 x 1 & 3.0 x 4
nysical secifications nvironment			C-Type x 1
	Speaker Type		Built-in Speaker
	Speaker Output		20W x 2
	Protection Glass		AG Toughened Glass
	Dimension (mm)	Gross	1670 x 225 x 1010
	Weight (kg)	Net	38
	meigint (kg)	Gross	48
	Cabinet Colour		Black
	Temperature		0-45°C
	Humidity		0-95%
wer	Power Supply		AC 100-240 Volt 50 Hz
	Certificate		ROHS, CE, FCC,BIS
	Detachable PC Module (Optional)		 Intel®CoreTM i5 / i7 - 11[®]& 12 Ĝen. Storage 128/256/512/1000 HDD/SSD Memory - 8 GB / 16 GB WiFi 802. 11ac (2.4 GHz/5GHz)
			• USB 2.0 / 3.0 • LAN RJ45 x 1 • Bluetooth 4.2
			Graphics - Integrated Intel®HD Graphics Sound - Integrated High Definition Audio Stereo Networking - Integrated 10/100/1000M Adaptor
			Microphone Input x 1 C-Type x1
	Standard Access		AC Power Cord, Remote Control, Wall Mount Bracket, VGA Cable, USB Cable, Audio/ Video Cables

