

Logibird Conference ePTZ Camera

LB-1030U3




4K



110° Wide-Angle



Microphone Array



USB 3.0



AI Humanoid Tracing


4k Ultra HD Imaging

Unlock Unlimited Creative Possibilities with Industry-Leading Driver Chips & Proprietary Algorithms



Features:

- ◆ Zoom: 4X Digital Zoom
- ◆ 4K@ 30fps, 1080p@ 30fps
- ◆ 110 Degree (W) field of view
- ◆ Video Output: USB 3.0
- ◆ Smart & Solid design
- ◆ 1/2.7", CMOS, Effective Pixel: 8.29M
- ◆ Pickup Distance of 6m
- ◆ Support H.264, MJPEG and YUY2



MULTI- INSTALLATION



Video Chat



Video Conference



Live Meeting

Product Specifications

Camera Specification

Sensor	1/2.7 inches, CMOS, Effective Pixels:8.29 Mega pixel
Scanning Mode	Progressive
Type of Lens Mount	M12
Lens	F=2.2mm, FOV: 110°
Minimum Illumination	0.5Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Bracket	Damping rotating bracket
Digital Noise Reduction	2D & 3D Digital Noise Reduction
Backlight Compensation	Support

I/O

USB Interface	1 x USB 3.0, type C
Remote Control	Support

Generic Spec.

Input Voltage	5V (USB Power Supply)
Input Current	0.6A (Max.)
Operating Temperature	0° C ~ 40° C
Storage Temperature	-40° C ~ 60° C
Power Consumption	3W (Max.)
Dimension	118mm (W)x 37.2mm (D)x 34.5mm (H) (Non -bracket)

USB Spec.

Operating System	Windows 7 (only support UVC1.1 features), Windows 8 and above version, MacOS 10.5 and above version, Linux 2.4.6 and above version, Android needs to include the version of UVC-related drivers.
Hardware Requirements	2.4 GHz Intel Core 2 Duo Processor or higher 2GB Memory or higher USB 2.0 (4K requirements USB 3.0)
Color System/Compression	H.264 / MJPEG / YUY2
Video Format	4K P30/25, 1080P30/25, 720P30/25, 960x540P30/25, 640x360P30/25 etc.
USB Video Communication Protocol	UVC 1.1
UVC PTZ Control	Support (EPTZ)

